

IP67 : Suitable for Near Water Locations IK10 : Impact Resistant (Vandal Resistant)

## Atlantis 1- S - Surface Flood LED

# 3.1" round - Near Water Marine Grade Stainless Steel 316

A range of high quality Stainless Steel near water surface mounted floodlight luminaires with a selection of different optics.

This surface mounted Luminaire manufactured from Marine Grade Stainless 316 and is designed for use in in areas of high corrosion as well as the possibility of seasonal flooding, near water falls, flood plains, docks, or applications in marine environments.

Not only is the housing made of the highest quality stainless steel but incorporated in the product design is a unique product feature that uses a water proof potting compound that totally seals the back of the luminaire and stops water ingress. This Luminaire is adjustable and has a tamper resistant locking feature.

#### Installer Friendly.

This product is be attached to the surface by securing the luminaire using the counter sink holes provided around the base of the luminaire.

A 16 foot low voltage water proof power cable is provided from the back of the luminaire that leads to the remote mounted driver or remote 24Vdc low voltage transformer provided by SLS.

Remote mounted box provided by contractor.

This product is also available with a underwater rating. Contact factory or SLS website for more information.

#### **Technical Data**

Fixture Marine Grade 316 Stainless Steel
Bracket Marine Grade 316 Stainless Steel
Hardware Marine Grade 316 Stainless Steel

Lens Tempered Glass
Optics 10°, 25°, 40°

**Driver** 120-277V 50-60Hz - remote mount

Optional Low Voltage 120VAC to 24VDC low voltage transformer - remote mount

LED Watts 1W, 3W

LED (white) 3300K, 4500K, 6000K
LED (static color) Red, Green, Amber or Blue

**Lumens** 70 lm, 150 lm **CRI** > 85


Cable 16 foot Water Proof Cable

Approvals ETL




Polished Finish

#### **Dimensions**



#### **Ground Spike**



ROJECT:		DATE:	QUANTITY:	Œ
YPF·	NOTE:			Inte



## **Atlantis 1-S - Surface Flood LED**

### 3.1" round - Near Water Marine Grade Stainless Steel 316





10°

Model (Specify) Wattage

1W 421260

3W 421270

100 lx

209 lx

3710 lx

266 lx


6.5 feet 618 lx

3 feet 2370 lx

1.6 feet 7540 lx

1 Watt Beam


3 Watt Beam





Lumens


70

150









#### **Options** (Specify)

**LED Color** (33K)3300K (45K) $\triangle$ 4500K (60K) 6000K Blue (BLU) (RED) Red Amber (AMB) (GRN) Green

(10)10° 25° (25)(40)40°

**Beam Spread** 

Lens (C) Clear (F) Frosted

Volts (UNV) 120/277V (DC) 24V DC

Other (GS) **Ground Spike** 

Ordering Example: Atlantis 1 - S - 421260 - 1W - 33K - 10 - C - DC

Code

**LED Watts** 

**LED Color** 

Beam

Lens

Volts

Other

Atlantis 1 - S -

PROJECT:

TYPE:

NOTE:

DATE:

QUANTITY:

