

IP67: Suitable for Near Water Locations IK10: Impact Resistant (Vandal Resistant)



## **Atlantis 2 - Surface Uplight LED**

## 3.3" round - Near Water Marine Grade Stainless Steel 316

A range of high quality Stainless Steel under water surface mounted floodlight luminaires with a selection of different optics.

This surface mounted Luminaire manufactured from Marine Grade Stainless 316 and is designed for use in in areas of high corrosion as well as the possibility of seasonal flooding, near water falls, flood plains, docks, or applications in marine environments.

Not only is the housing made of the highest quality stainless steel but incorporated in the product design is a unique product feature that uses a water proof potting compound that totally seals the back of the luminaire and stops water ingress.

#### Installer Friendly.

This product is be attached to the surface by securing the luminaire using the counter sink holes provided around the base of the luminaire.

A 16 foot low voltage water proof power cable is provided from the back of the luminaire that leads to the remote mounted driver or remote 24Vdc low voltage transformer provided by SLS.

Remote mounted box provided by contractor.

This product is available with a under water or outdoor rating. Contact factory or SLS website for more information



**Fixture** Marine Grade 316 Stainless Steel **Bracket** Marine Grade 316 Stainless Steel Marine Grade 316 Stainless Steel Hardware

Lens Tempered Glass 10°, 25°, 40° **Optics** 

Driver 120-277V 50-60Hz - remote mount

Low Voltage (Optional) 120VAC to 24VDC low voltage transformer - remote mount

**LED Watts** 


3300K, 4500K, 6000K LED (white) LED (static color) Red, Green, Amber or Blue

Lumens 210 lm, 450 lm


CRI > 85


Cable 16 foot Water Proof Cable

FTI **Approvals** 



Polished Finish








# **Atlantis 2 - Surface Uplight LED**

3.3" round - Near Water Marine Grade Stainless Steel 316





Wattage	Round (Specify)	Lumens
3W	412230	210
9W	421370	450




122 lx


333 lx

3 feet 3580 lx

9 Watt Beam

TYPE:







(BE)


15 lx

(SE)



10





### **Options** (Specify)



	Cable Entry	
(BE)	Bottom	
(SE)	Side	
	Beam Spread	
(10)	10°	

	Lens	
(40)	40°	
(25)	25°	
(10)	10°	

(C)	Clear		
(F)	Frosted		
` ,			
	Volts		
(UNV)	120/277V		


(DC)

24V DC

Ordering Example: Atlantis 2 - 421370 - 9W - 33K - BE - 10 - C - UNV

Code **LED Watts LED Color** Entry Beam Lens Volts Atlantis 2 -

PROJECT:		





NOTE: