



IP68 : Suitable for Underwater Locations
IK10 : Impact Resistant (Vandal Resistant)

Atlantis 2 - Surface Uplight LED

3.3" round - Underwater Marine Grade Stainless Steel 316

A range of high quality Stainless Steel under water surface mounted floodlight Luminaires with a selection of different optics.

This surface mounted Luminaire manufactured from Marine Grade Stainless 316 and is designed for use in areas of high corrosion as well as the possibility of seasonal flooding, near water falls, flood plains, docks, or applications in marine environments.

Not only is the housing made of the highest quality stainless steel but incorporated in the product design is a unique product feature that uses a water proof potting compound that totally seals the back of the luminaire and stops water ingress. This Luminaire is adjustable and has a tamper resistant locking feature.

Installer Friendly.

This product is be attached to the surface by securing the luminaire using the counter sink holes provided around the base of the luminaire.

A 16 foot low voltage water proof power cable is provided from the back of the luminaire that leads to the remote mounted driver or remote 24Vdc low voltage transformer provided by SLS.

Remote mounted box provided by contractor.



This product is available with a near water or outdoor rating. Contact factory or SLS website for more information.

Technical Data


Fixture	Marine Grade 316 Stainless Steel
Bracket	Marine Grade 316 Stainless Steel
Hardware	Marine Grade 316 Stainless Steel
Lens	Tempered Glass
Driver	120-277V 50-60Hz - remote mount
Low Voltage (optional)	120VAC to 24VDC low voltage transformer - remote mount
LED Watts	3W, 9W
LED (white)	3300K, 4500K, 6000K
LED (static color)	Red, Green, Amber or Blue
CRI	> 85
Cable	16 foot Water Proof Cable
Approvals	ETL



Polished Finish



Bottom Cable
Entry



Side Cable
Entry

PROJECT: _____

DATE: _____

QUANTITY: _____

TYPE: _____

NOTE: _____






Atlantis 2 - Surface Uplight LED

3.3" round - Underwater
Marine Grade Stainless Steel 316

3.3" Diameter

0° Tilt



Wattage	Round (Specify)	Lumens
3W	405370	210
9W	421330	450

Options (Specify)

	LED Color
(33K)	3300K
(45K)	4500K
(60K)	6000K
(BLU)	Blue
(RED)	Red
(AMB)	Amber
(GRN)	Green

Cable Entry

(BE)	Bottom
(SE)	Side

Beam Spread







(10)	10°
(25)	25°
(40)	40°

Lens

(C)	Clear
(F)	Frosted

Volts

(UNV)	120/277V
(DC)	24V DC



Ordering Example : Atlantis 2 - 421330 - 9W - 33K - BE - 10 - C - DC

Code

LED Watts

LED Color

Entry

Beam

Lens

Volts

Atlantis 2 -

PROJECT: _____

DATE: _____

QUANTITY: _____

TYPE: _____

NOTE: _____

Specialized Lighting Solutions reserves the right to change specifications without prior notice, please contact factory for latest information.

Specialized Lighting Solutions, LLC
7144 NE Progress Ct
Hillsboro, OR 97124

Tel: 503-530-8908
Fax: 503-531-0711

www.slsnw.com
09/11/18

